

Aequator Brasil I



Material

Varnished PUR front,
stainless steel side covers

Dimension

W 320, D 550, H 810 mm

Weight

50 kg net

Electricity

230 V, 50 Hz, 13 A
3 kW

Output

120 – 150 cups per hour
28 l hot water per hour

Target location

leisure, commercial and
professional sites requiring
vend capacity starting from
60 cups per day

Description

- 1 variety of coffee beans (option: machine with 2 grinders for 2 varieties of coffee beans)
- 2 instant containers for milk and chocolate
- 8 to 14 possible selections for hot drinks like coffee, espresso, latte macchiato, milk, tea, chocolate, cappuccino, ...
- illuminated branding and menu-guided display
- capacity of bean hopper for about 200 cups of coffee
- outlet adjustable, height from 100 to 150 mm
- water connection for fresh water, drip tray for waste water
optional: connection for waste water

Accessories

- optional payment systems: coin checker, coin changer, cashless (MDB/parallel) and interface for cash registers
- cup heater with storage room for up to 70 cups (W 250, D 370, H 785 mm)

USP's

- strong grinder for best coffee quality and durable safe operation
- Quali Control System: stable brewing speed due to automatic grinder control = constant coffee quality in the cup
- Hot Start System: 1st coffee always hot, also espresso (unique heating system)
- Hygo Milk Dry System: HACCP approved
- plastic brewing unit – low maintenance costs, no temperature loss while brewing
- little storage room needed for your milk supply because 1 bag of milk topping makes 5.0 litres of liquid milk. Durability of 1 year
- easy take out of instant containers to fill them and to clean the interior of the machine

